

**SPECIFICATIONS**

Model Numbers ..... 2102  
 \*Horsepower (B.I.A.-certified) ..... 2 hp at 4500 rpm  
 Full throttle operating range ..... 4000 to 5000 rpm  
 Test tank with test wheel ..... 4100 RPM  
 Test wheel ..... Part Number 314206  
 Engine type ..... Single cylinder, 2 cycle  
 Bore and stroke ..... 1-9/16" bore x 1-3/8" stroke  
 Piston displacement ..... 2.64 cubic inches  
 Piston ring sets (2 per set)  
     Standard ..... Part Number 383920  
     .030" oversize ..... Part Number 384312  
 Diameter of ring ..... 1.563 in. (standard)  
 Width of ring ..... .0625 - .0615 in.  
 Lbs. compression recommended when compressed .... 1.3 to 2.8 lbs.  
 Piston and rings - standard ..... Part Number 384651  
     .030" oversize piston less rings ..... Part Number 384666  
 Crankshaft size  
     Top journal ..... .7502 - .7497 in.  
     Bottom journal ..... .7502 - .7497 in.  
 Connecting rod crank pin ..... .6690 - .6685 in.  
 Carburetion ..... Single barrel float feed, with high and low-speed adjustments  
 Float level setting ..... Flush with casting  
 Inlet needle seat ..... .050 - .053 Use a #55 drill as gage  
 Cooling system ..... Centri-matic pump  
 Propeller gear ratio ..... 12:25  
 Propeller drive pin ..... Part Number 203230  
 Propeller ..... 7-1/4 x 4-1/2  
 Speed control ..... Single lever, synchronized throttle and spark  
 Weight ..... 23 lbs.  
 Fuel capacity ..... Gravity feed integral tank 1 qt.  
 Starter ..... Manual self rewinding  
 Ignition ..... Flywheel magneto  
 Spark plug ..... AC-M44C, Champion J6J - 14mm  
 Spark plug gap ..... .030 inch  
 Spark plug torque ..... 17-1/2 - 20-1/2 foot-pounds  
 Breaker point gap ..... .020 inch  
 Condenser ..... Part Number 580321  
     Capacity ..... .18 to .22 Mfd.

Part No. 580416 Coil Test Specifications  
 Old Stevens Tester

Switch	Index Reading
A	2. to 2.5

New Stevens Tester Model No. M.A. -75

Switch	Index Adjustment
A	22

Merc-O-Tronic

Operating Amperage	Primary Resistance		Secondary Continuity	
	Min.	Max.	Min.	Max.
1.4	.45	.55	35	45

Graham Tester Model 51

Maximum Secondary	Maximum Primary	Coil Index	Minimum Coil Test	Gap Index
5500	1.2	75	33	70

\* Horsepower established at sea level. Allow 2% reduction per 1000' above sea level.