

SPECIFICATIONS

Model	4206, (Lightwin, weedless, gearcase) 4236, (Yachtwin, standard gearcase)	Propeller gear ratio	17:28 Lightwin 12:25 Yachtwin										
*Horsepower (B.I.A. - certified)	4 hp at 4500 rpm	Propeller drive pin	Part Number 203230 1/8" x 13/16" stainless steel										
Full throttle op.-range	4000 to 5000 rpm	Propeller	Yachtwin - Standard - 8" diameter x 5-1/2" pitch, 3 blade Optional - 8" x 4-1/2", 3 blade Lightwin - 6-1/4" diameter x 5-1/2" pitch, 3 blades										
Test tank rpm with test wheel	4100 rpm Part Number 316021 for 4206, 4207 Part Number 316960 for 4236, 4237	Speed control	Single lever, synchronized throttle and spark										
Engine type	2-cylinder, 2 cycle alternate firing	Weight	4206 Model - 34.0 lbs. 4236 Model - 34.5 lbs.										
Bore and stroke	1-9/16" bore x 1-3/8" stroke	Hi Lift vacuum fuel system	3 gal. tank and plug in hose										
Piston displacement	5.28 cubic inches	Fuel capacity	3 gallons										
Piston ring sets (2 per set) standard .030" oversize	Part Number 383920 Part Number 384312	Starter	Eas-A-Matic, self-rewinding										
Diameter of ring	1.563 in. (standard)	Ignition	Flywheel magneto										
Width of ring	.0625 - .0615 in.	Spark plug	AC-M44C, Champion J6J, - 14mm										
Lbs. compression recommended when compressed	1.3 to 2.8 lbs.	Spark plug gap	.030 inch										
Piston and ring assembly standard .030" oversize	Part Number 384651 Part Number 384666	Spark plug torque	17-1/2 - 20-1/2 foot-pounds										
Crankshaft size top journal center journal bottom journal	.7520 - .7515 in. .6854 - .6849 in. .6854 - .6849 in.	Breaker point gap	.020 inch										
Connecting rod crank pin	.6255 - .6250 in.	Condenser Capacity	Part Number 580321 .18 to .22 Mfd.										
Carburetion	Single barrel float feed, with high and low-speed adjustments manual choke	COIL SPECIFICATIONS											
Float level setting	Flush with casting	Part No. 580416 Coil Test Specifications:											
Inlet needle seat	.053 - .050 Use a #55 drill as gage.	Old Stevens Tester											
Cooling system	Centri-matic (combination positive displacement and centrifugal pump).	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 30%;">Switch</th> <th style="width: 70%;">Index Reading</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">A</td> <td style="text-align: center;">2.0 - 2.5</td> </tr> </tbody> </table>		Switch	Index Reading	A	2.0 - 2.5						
Switch	Index Reading												
A	2.0 - 2.5												
		New Stevens Tester Model No. M.A.-75											
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 30%;">Switch</th> <th style="width: 70%;">Index Adjustment</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">A</td> <td style="text-align: center;">22</td> </tr> </tbody> </table>		Switch	Index Adjustment	A	22						
Switch	Index Adjustment												
A	22												
		Merc-O-Tronic											
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 30%;">Operating Amperage</th> <th style="width: 30%;">Primary Resistance Min. Max.</th> <th style="width: 40%;">Secondary Continuity Min. Max.</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1.4</td> <td style="text-align: center;">.45 - .55</td> <td style="text-align: center;">35 - 45</td> </tr> </tbody> </table>		Operating Amperage	Primary Resistance Min. Max.	Secondary Continuity Min. Max.	1.4	.45 - .55	35 - 45				
Operating Amperage	Primary Resistance Min. Max.	Secondary Continuity Min. Max.											
1.4	.45 - .55	35 - 45											
		Graham Tester Model 51											
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 20%;">Maximum Secondary</th> <th style="width: 15%;">Maximum Primary</th> <th style="width: 15%;">Coil Index</th> <th style="width: 20%;">Minimum Coil Test</th> <th style="width: 30%;">Gap Index</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">5500</td> <td style="text-align: center;">1.2</td> <td style="text-align: center;">75</td> <td style="text-align: center;">33</td> <td style="text-align: center;">70</td> </tr> </tbody> </table>		Maximum Secondary	Maximum Primary	Coil Index	Minimum Coil Test	Gap Index	5500	1.2	75	33	70
Maximum Secondary	Maximum Primary	Coil Index	Minimum Coil Test	Gap Index									
5500	1.2	75	33	70									

*Horsepower established at sea level. Allow 2% reduction per 1000' above sea level.