

SPECIFICATIONS UNIQUE TO HORSEPOWER

| | |
|---|---|
| Model Numbers 85793, 85799 20" (508 mm) transom | Model Numbers 115793, 115799 20" (508 mm) transom |
| *Horsepower (B.I.A.- certified) 85 hp at 5000 rpm | *Horsepower (B.I.A.- certified) 115 hp at 5000 rpm |
| Bore and stroke - 85 hp. . 3-3/8" bore x 2-19/32" stroke (85.72 x 65.88 mm) | Bore and stroke - 115 hp 3-1/2" bore x 2-19/32" stroke (88.90 x 65.88 mm) |
| Piston displacement 92.6 cu. in. (1517 cm ³) | Piston displacement - 115 hp 99.6 cu. in. (1632 cm ³) |
| Piston ring sets (3 per set) standard - 85 hp Part No. 385666 .030" oversize Part No. 386331 | Piston ring sets (3 per set) standard - 115 hp Part No. 385661 .020" oversize Part No. 385662 .030" oversize Part No. 385663 |
| Diameter of standard - 85 hp ring 3.375" (85.72 mm) | Diameter of standard - 115 hp ring 3.500" (88.90 mm) |
| Width of ring (upper) . . . 0.0895" - 0.0900" (2.273 - 2.286 mm) (lower) . . . 0.0615" - 0.0625" (1.562 - 1.588 mm) | Width of ring (upper) . . . 0.0895" - 0.0900" (2.273 - 2.286 mm) (lower) . . . 0.0615" - 0.0625" (1.562 - 1.588 mm) |
| Piston less rings Standard - 85 hp Part No. 386301 .030" oversize Part No. 386331 | Piston less rings Standard - 115 hp Part No. 386300 .020" oversize Part No. 386330 .030" oversize Part No. 386329 |
| Carburetor high speed orifice plug - 85 hp Part No. 322221 Hole size 0.049" (1.24 mm) | Carburetor high speed orifice plug - 115 hp Part No. 317330 Hole size 0.059" (1.50 mm) |
| Carburetor low speed orifice plug - 85 hp Part No. 323003 Hole size 0.025" (0.64 mm) | Carburetor low speed orifice plug - 115 hp Part No. 322776 Hole size 0.029" (0.74 mm) |
| Timing - 85 hp . . . 26° @ 4300-4600 rpm in gear | Timing - 115 hp . . . 28° @ 4300-4600 rpm in gear |
| Propeller supplied with motor - 85 hp. . Aluminum 3 blade, 13-1/4" dia. x 17" pitch | Propeller supplied with motor Aluminum 3 blade, 13" dia. x 19" pitch |
| Tank test with test wheel Part No. 382861 4800 rpm | Tank test with test wheel Part No. 384933 4800 rpm |

*Horsepower established at sea level. Allow 2% reduction per 1000' (300 m) above sea level.