

REFERENCE INFORMATION
SERVICE SPECIFICATIONS

SERVICE SPECIFICATIONS

	HP	115, 130	150, 175, 200	
	Full Throttle Operating Range	5500–6000 RPM	4850–5850 RPM	
	Power	115 HP: (85.8 kw) @ 5750 RPM 130 HP: (96.9 kw) @ 5750 RPM	150 HP: (111.9 kw) @ 5350 RPM 175 HP: (130.5 kw) @ 5350 RPM 200 HP: (149.1 kw) @ 5350 RPM	
	Idle RPM in Gear	115: 625 ± 50 115 HO, 130: 580 ± 50	500 ± 50	
	Test Propeller	V4 20 in. (L) Models: P/N 386246 or P/N 433068 V4 25 in. (X) and V6 Standard Rotation Models: P/N 387388 V6 Counter Rotation Models: P/N 398673		
ENGINE	Weight (may vary depending on model)	115-20 in. (L): 375 lbs. (170 kg) 115 HO, 130-20 in. (L): 390 lbs. (177 kg) 115-25 in. (X): 390 lbs. (177 kg) 115 HO, 130-25 in. (X): 405 lbs. (184 kg)	20 in. (L): 418 lbs. (190 kg) 25 in. (X): 433 lbs. (196 kg)	
	Lubrication	<i>Evinrude/Johnson XD100 Oil</i> or <i>Evinrude/Johnson XD50 Oil</i> Refer to Recommended Lubricants on p. 168		
	Engine Type	60° V 4-Cylinder Loop-Charged	60° V 6-Cylinder Loop-Charged	
	Displacement	105.4 cu. in. (1727 cm ³)	158.2 cu. in. (2592 cm ³)	
	Bore	3.601 in (91.47 mm)		
	Stroke	2.588 in. (65.74 mm)		
	Standard Bore	3.6005 to 3.6015 in. (91.45 to 91.48 mm)		
	Top Crankshaft Journal	2.1870 to 2.1875 in. (55.55 to 55.56 mm)		
	Center Crankshaft Journals	2.1870 to 2.1875 in. (55.55 to 55.56 mm)		
	Bottom Crankshaft Journal	1.5747 to 1.5752 in. (40.0 to 40.01 mm)		
	Rod Crankpin	1.3757 to 1.3762 in. (34.94 to 34.96 mm)		
	Piston Ring End Gap, Both	0.011 to 0.023 in. (0.28 to 0.58 mm)		
	FUEL	Fuel/Oil Ratio	<i>EMM</i> Controlled	
		Starting Enrichment	<i>EMM</i> Controlled	
		Preferred Fuel	Regular unleaded gasoline	
		Acceptable Fuel	See Fuel Requirements on p. 137 for additional information.	
		Minimum (High) Fuel Pressure @ IDLE RPM – 500 ± 50	22 to 28 psi (152 to 193 kPa)	
		Minimum Fuel Lift Pump Pressure @ IDLE RPM – 500 ± 50	3 to 4 psi (21 to 28 kPa)	
		Maximum Fuel Inlet Vacuum	4 in. Hg. (13.5 kPa)	
Minimum Octane		87 AKI (R+M)/2 or 90 RON		
Additives		<i>2+4</i> ® Fuel Conditioner, Fuel System Cleaner Use of other additives may result in engine damage. See Fuel Requirements on p. 137 for additional information.		

REFERENCE INFORMATION
SERVICE SPECIFICATIONS

1

	HP	115, 130	150, 175, 200
ELECTRICAL	Minimum Battery Requirements	675 CCA (845 MCA); or 750 CCA (940 MCA) below 32°F (0°C) (Use a 107 amp-hr battery for extreme applications.)	
	Alternator	Dual Voltage 50 Amp with Voltage Regulator and Battery Isolation. Refer to Predelivery and Installation Guide for multiple battery applications.	
	Tachometer Setting	6 pulse (12 pole)	
	Charging Isolator	Integral, Terminal on Engine Harness	
	Engine Fuse	P/N 967545 – 10 A	
COOLING	Thermostat	143°F (62°C)	
	Maximum Temperature	230°F (110°C) Below 3000 RPM and 194°F (90°C) Above 3000 RPM	
	Water pressure	V4: 21 to 23 psi @ 5000 RPM V6: 23 to 25 psi @ 5000 RPM	
IGNITION	Type	Capacitor Discharge	
	Firing Order	1-2-3-4	1-2-3-4-5-6
	Ignition Features	EMM Controlled	
	RPM Limit	6250	
	Crankshaft Position Sensor Air Gap	Fixed	
	Spark Plug	Refer to Emission Control Information Label Champion [†] QC10WEP @ 0.028 ± 0.003 in. (0.76 mm) Refer to Emission Control Information Label	
GEARCASE	Gear Ratio	V4 “S2” Type Gearcase: 13:26 (.500) (2:1) V4 “O” Type Gearcase: 12:27 (.444) (2.25:1) V6 “O” Type Gearcase: 14:26 (.538) (1.86:1) V6 “M2” Type Gearcase: 13:24 (.542) (1.85:1) V6 “L2” Type Gearcase: 14:26 (.538) (1.86:1) Refer to GEARCASE TYPES on p. 263	
	Lubricant	HPF XR Gearcase Lubricant	
	Capacity	“S2” Type Gearcase: 31.6 fl. oz. (935 ml) V4 “O” Type Gearcase: 32.8 fl. oz. (970 ml) V6 “O” Type Gearcase: 33.1 fl. oz. (980 ml) “M2” Type Gearcase: 38.9 fl. oz. (1150 ml) “M2” Type – Counter Rotation: 35.8 fl. oz. (1060 ml) “L2” Type Gearcase: 32.5 fl. oz. (960 ml)	
	Shift Rod Height	20 in. (L) Models: 20.945 (532 mm) ± one-half turn 25 in. (X) Models: 25.945 (659 mm) ± one-half turn	
	Shift Cable Stroke	1.125 to 1.330 in. (28.6 to 33.8 mm) measured between NEUTRAL and FORWARD	
POWER TRIM/TILT	Lubrication	(Single Piston style): Evinrude/Johnson Biodegradable TNT Fluid (Three Piston style): Evinrude/Johnson Power Trim/Tilt & Power Steering Fluid or GM Dextron [†] II Automatic Transmission Fluid	
	Fluid Capacity	21 fl. oz. (622ml)	
	Trim Range	0° to 21°	
	Tilt Range	22° to 75°	