

SPECIFICATIONS

Model Numbers	9R71 - Standard length (15" transom) 9RL71 - 5" longer (20" transom)	Speed control	On steering handle, synchronized throttle and spark											
*Horsepower (B.I.A. - certified)	9-1/2 hp at 4500 rpm	Gear shift control	Forward, neutral, & reverse											
Full throttle operating range	4000 to 5000 rpm	Weight	Model 9R71 - 60 lbs Model 9RL71 - 61 lbs (without fuel tank) (fuel tank weight 11 pounds net)											
Tank test with test wheel	Part No. 379673 4400 rpm	Fuel capacity	6 gallons											
Engine type	2 cylinder, 2 cycle alternate firing	Starter	Manual - self rewind											
Bore and stroke	2-5/16" bore x 1-13/16" stroke	Ignition	Flywheel magneto											
Piston displacement	15.2 cubic inches	Spark plug	AC-M42K, Champion J4J - 14mm											
Piston ring sets (3 per set)		Spark plug gap	.030 inch											
standard	Part No. 379360	Spark plug torque	17-1/2 - 20-1/2 foot-pounds											
.030" oversize	Part No. 384073	Breaker point gap	.020 inch											
Diameter of ring	2.3125" (standard)	Condenser Capacity	Part Number 580321 .18 - .22 mfd.											
Width of ring	.0935" - .0925"	Part No. 580416 Coil Test Specifications												
Lbs. compression recommended when compressed	3 to 5 lbs.	Old Stevens Tester												
Piston less rings standard	Part No. 379134	<table border="1"> <thead> <tr> <th>Switch</th> <th>Index Reading</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>2.0 - 2.5</td> </tr> </tbody> </table>			Switch	Index Reading	A	2.0 - 2.5						
Switch	Index Reading													
A	2.0 - 2.5													
.030" oversize	Part No. 384072	New Stevens Tester Model No. M.A.-75												
Crankshaft size top journal	.8125" - .8120"	<table border="1"> <thead> <tr> <th>Switch</th> <th>Index Adjustment</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>22</td> </tr> </tbody> </table>			Switch	Index Adjustment	A	22						
Switch	Index Adjustment													
A	22													
center journal	.8132" - .8127"	Merc-O-Tronic												
bottom journal	.8125" - .8120"	<table border="1"> <thead> <tr> <th>Operating Amperage</th> <th>Primary Resistance Min. - Max.</th> <th>Secondary Continuity Min. - Max.</th> </tr> </thead> <tbody> <tr> <td>1.4</td> <td>.45 - .55</td> <td>35 - 45</td> </tr> </tbody> </table>			Operating Amperage	Primary Resistance Min. - Max.	Secondary Continuity Min. - Max.	1.4	.45 - .55	35 - 45				
Operating Amperage	Primary Resistance Min. - Max.	Secondary Continuity Min. - Max.												
1.4	.45 - .55	35 - 45												
Connecting rod crank pin	.8132" - .8127"	Graham Tester Model 51												
Cooling system	Vari-Volume (combination positive displacement & centrifugal pump) thermostatically controlled	<table border="1"> <thead> <tr> <th>Maximum Secondary</th> <th>Maximum Primary</th> <th>Coil Index</th> <th>Minimum Coil Test</th> <th>Gap Index</th> </tr> </thead> <tbody> <tr> <td>5500</td> <td>1.2</td> <td>75</td> <td>33</td> <td>70</td> </tr> </tbody> </table>			Maximum Secondary	Maximum Primary	Coil Index	Minimum Coil Test	Gap Index	5500	1.2	75	33	70
Maximum Secondary	Maximum Primary	Coil Index	Minimum Coil Test	Gap Index										
5500	1.2	75	33	70										
Carburetion	Float feed, low-speed adjustment and manual choke													
Float level setting	Parallel with face of casting													
Carburetor orifice plug	Hole size - .048". Use a #56 drill as gage.													
Inlet needle seat	.053" - .050". Use a #55 drill as gage.													
Propeller gear ratio	13:23													
Propeller drive pin	Part No. 307949 3/16" x 1-25/64" stainless steel													
Propeller	3 Blade, 8-1/8" dia. x 8" Pitch													

*Horsepower established at sea level. Allow 2% reduction per 1000' above sea level.

CLEARANCE CHART

POWER HEAD			
Piston and wrist pin - loose end	.0005 Max. - .0000 Min.	Driveshaft - upper	.0020 Max. - .0003 Min.
Piston ring gap	.017 Max. - .007 Min.	Propeller on shaft	.009 Max. - .007 Min.
Piston ring groove clearance	.0035 Max. - .001 Min.	Front gear to gearcase bearing	.0022 Max. - .0010 Min.
Cylinder and piston	.0050 Max. - .0035 Min.	Front gear to front bushing	Press fit
Crankshaft bearings		Front gear bushing to propeller shaft	.0015 Max. - .0005 Min.
Upper	Roller bearing	Rear reverse gear to rear bushing	.0020 Max. - .0005 Min.
Center	Needle bearing		
Lower	Needle bearing		
Connecting rod bearings			
Piston end	Needle bearing		
Crankshaft end	Needle bearing		
LOWER UNIT			
Gearcase head and propeller shaft	.0020 Max. - .0010 Min.	Rear gear bushing to propeller shaft	.0015 Max. - .0005 Min.

TORQUE CHART

POWER HEAD		STANDARD SCREWS		
Flywheel nut	40-45 Foot-pounds		Inch-Pounds	Foot-Pounds
Connecting rod screws	90-100 Inch-pounds	No. 6	7-10	
Cylinder head screws	96-120 Inch-pounds	No. 8	15-22	
Crankcase to cylinder screws		No. 10	25-35	2-3
Upper	120-145 Inch-pounds	No. 12	35-40	3-4
Center	120-145 Inch-pounds	1/4"	60-80	5-7
Lower	120-145 Inch-pounds	5/16"	120-140	10-12
Spark plugs	17-1/2 - 20-1/2 Foot-pounds	3/8"	220-240	18-20
LOWER UNIT		<p>When tightening two or more screws on the same part, DO NOT tighten screws completely, one at a time. To avoid distortion of the part, first tighten all screws together to one-third of specified torque, then to two-thirds of specified torque, then torque down completely.</p>		
Side mount nuts - upper & lower	150 to 170 Inch-pounds (12 to 14 Foot-pounds)	NOTE		
Slip clutch propeller	70 Foot-pounds	<p>Re-check torque on cylinder head screws and spark plugs after motor test has been completed and motor has cooled comfortable to touch.</p>		