

NOTE

The recommended full power operating range for your outboard motor is from 4500 - 5500 R.P.M. In order to get the best performance from your outboard the upper end of this range, from 5000 - 5500 R.P.M., is the engine speed to use in selecting the proper propeller. The R.P.M. should be measured with your expected average load in the boat.

SPECIFICATIONS

Model Numbers	85ESL75 (20" transom)
*Horsepower (B.I.A.-certified)	85 hp at 5000 rpm
Full throttle operating range	4500 to 5500 rpm
Tank test with test wheel Part Number 382861	4800 rpm
Engine type	90° V-type, 4 cylinder, 2 cycle
Bore and stroke	3-3/8" bore x 2-19/32" stroke
Piston displacement	92.6 cubic inches
Piston ring sets (3 per set) standard	Part Number 385664
.030" oversize	Part Number 385666
Diameter of ring	3.375 in. (standard)
Width of ring (upper)0900 - .0895 in.
(lower)0615 - .0625 in.
Piston ring lbs. compression recommended when compressed (upper)	1.0 - 3.0 lbs.
(lower)	3.3 - 4.9 lbs.
Piston less rings Standard	Part Number 386301
.030" oversize	Part Number 386331
Crankshaft size Top journal	1.6204 - 1.6199
Center journals	1.3752 - 1.3748
Bottom journal	1.3784 - 1.3779
Connecting rod crank pin	1.3762 - 1.3757
Carburetion	2 carburetors - Float feed with fixed high and low-speed jets, Automatic, manual lever and remote control choke
Float level setting	Remove float bowl, turn carburetor upside down so weight of float closes needle; float should now be parallel to gasket surface.
Carburetor high speed orifice plug	Part Number 317646 Hole size .054 in.
Carburetor low speed orifice plug	Part Number 317474 Hole size .027 in.
Inlet needle seat065 - .062 Use a #52 drill as gage
Cooling system	Thermostatically controlled re-circulating system
Propeller gear ratio	13:26
Propeller supplied with motor	Aluminum 3 blade, 13-1/4" dia. x 17" pitch
Alternate propellers	Aluminum 3 blade, 14" dia. x 11" pitch
	Aluminum 3 blade, 14" dia. x 13" pitch
	Aluminum 3 blade, 13-3/4" dia. x 15" pitch
	Aluminum 3 blade, 13" dia. x 19" pitch
	Aluminum 3 blade, 12-3/4" dia. x 21" pitch
	Aluminum 3 blade, 12-3/4" dia. x 23" pitch
	Bronze 2 blade, 13-3/4" dia. x 21" pitch
	Bronze 2 blade cupped, 13-3/4" dia. x 21" pitch
	Bronze 2 blade cupped, 13-3/4" dia. x 23" pitch
	Stainless steel 3 blade, 13-3/4" dia. x 15" pitch
	Stainless steel 3 blade, 13-1/4" dia. x 17" pitch
	Stainless steel 3 blade, 13" dia. x 19" pitch
	Stainless steel 3 blade, 12-3/4" dia. x 21" pitch
	Stainless steel 3 blade, 12-3/4" dia. x 23" pitch
Speed control	Remote control - Synchronized throttle and spark
Gear shift control	COMMAND CENTER - forward, neutral, reverse - remote control
Weight (without fuel tank)	267 lbs. (Fuel tank weight 11 lbs. net)
Fuel capacity	6 gallons
Starter	Electric and emergency rope
Starter amp draw when cranking (Prestolite)	180 amps maximum
(Bosch)	160 amps maximum
Starter RPM	250 RPM for ignition
Generator system	6 ampere flywheel alternator
Ignition (Magneto breakerless C.D.)	Power Pack
Timing	26° @ 4300-4600 RPM in gear
Spark plug	Champion L77J4 or AC-M40FFX
Spark plug gap040"
Spark plug torque	17-1/2" - 20-1/2" foot-pounds
Sensor air gap	Fixed
Coil	Part Number 581032

*Horsepower established at sea level. Allow 2% reduction per 1000' above sea level.