

SPECIAL TOOLS AND SERVICE SPECIFICATIONS
TECHNICAL DATA

TECHNICAL DATA

	HP	90, 105, 115	150, 175
ENGINE	Full Throttle Operating Range RPM	4500–5500	
	Power	90 HP (67.2 kw) @ 5000 RPM 115 HP (85.8 kw) @ 5000 RPM	150 HP (112 kw) @ 5000 175 HP (131 kw) @ 5000
	Idle RPM in Gear	650 ± 50	
	Weight	20 in. (L) Models: 335 lbs. (152 kg) 25 in. (X) Models: 352 lbs. (160 kg)	20 in. (L) Models: 383 lbs. (174 kg) 25 in. (X) Models: 391 lbs. (177 kg)
	Lubrication	<i>Evinrude/Johnson XD25 Formula Outboard Oil</i> Refer to Engine Lubricant , this section.	
	Engine Type	60° V 4-Cyl Loop-Charged	60° V 6-Cyl Loop-Charged
	Displacement	105.4 cu. in. (1726 cm ³)	158 cu. in. (2589 cm ³)
	Bore	3.600 in (91.44 mm)	
	Stroke	2.588 in. (65.74 mm)	
	Standard Bore	3.6005 to 3.6015 in. (91.45 to 91.48 mm) To bore oversize, add piston oversize dimension to standard bore	
	Top Crankshaft Journal	2.1870 to 2.1875 in. (55.55 to 55.56 mm)	
	Center Crankshaft Journals	2.1870 to 2.1875 in. (55.55 to 55.56 mm)	
	Bottom Crankshaft Journal	1.5747 to 1.5752 in. (40.0 to 40.01 mm)	
	Rod Crankpin	1.3757 to 1.3762 in. (34.94 to 34.96 mm)	
	Piston Ring End Gap, Both	0.011 to 0.023 in. (0.28 to 0.58 mm)	
	Test Propeller	PL, VL, GL – P/N 386246 or P/N 433068 PX, WPL – P/N 387388	PL, VL, GL – P/N 387388 CX – P/N 398673
	FUEL	Fuel/Oil Ratio	Controlled by oil injection system
Carburetion		Two dual-throat carburetors, float feed	Two triple-throat carburetors, float feed
Calibration		Adjustable slow speed, fixed intermediate and high speed	
Needle Valve Setting		Refer to FUEL SYSTEM section	
Starting Enrichment		Electric primer solenoid	
Carburetor Float Level Setting		Level with gasket surface ± 0.03 in. (0.8 mm), chamber inverted	
Carburetor Float Drop Setting		11/16 to 1 1/8 in. (17 to 28 mm)	
Vapor Separator Float Level Setting		Parallel with Separator Body	
Vapor Separator Float Drop Setting		1 1/4 to 1 11/32 in. (32 to 34 mm)	
Preferred Fuel		Regular unleaded, mid-grade unleaded, premium unleaded gasolines	
Acceptable Fuel		Any of the above gasolines with 10% Ethanol or 5% Methanol with 5% co-solvents	
Minimum Octane		87 AKI (R+M)/2 or 90 RON	
Additives	2+4 Fuel Conditioner, Fuel System Cleaner, Carbon Guard Use of other additives may result in engine damage.		
	See FUEL REQUIREMENTS , this section, for additional information		