

SPECIFICATIONS

Item	Unit	Data	
		40	50

DIMENSIONS AND WEIGHT

Overall length (front to back)		mm (in)	756 (29.8)
Overall width (side to side)		mm (in)	382 (15.0)
Overall height	S	mm (in)	1263 (49.7)
	L	mm (in)	1390 (54.7)
Weight (without engine oil)	S	kg (lbs)	106 (234)
	L	kg (lbs)	109 (240)
Transom height	S	mm (in type)	401 (15)
	L	mm (in type)	528 (20)

PERFORMANCE

Maximum output	kW (HP)	29.4 (40)	36.8 (50)
Recommended operating range	r/min	5200 – 5800	5900 – 6500
Idle speed	r/min	850 ± 50 (in-gear: approx. 850)	

POWERHEAD

Engine type		4-stroke DOHC
Number of cylinders		3
Bore	mm (in)	71.0 (2.80)
Stroke	mm (in)	68.6 (2.70)
Total displacement	cm ³ (cu in)	815 (49.7)
Compression ratio	: 1	10
Spark plug	NGK	DCPR6E
Ignition system		Full-transistorized ignition
Fuel supply system		Multi-point sequential electronic fuel injection
Exhaust system		Through prop exhaust
Cooling system		Water cooled
Lubrication system		Wet sump by trochoid pump
Starting system		Electric
Throttle control		Remote control