

*SPECIFICATIONS

*These specifications are subject to change without notice.

Item	Unit	Data	
		60	70

DIMENSIONS AND WEIGHT

Overall length (front to back)	mm (in)	795 (31.3)	795 (31.3)
Overall width (side to side)	mm (in)	435 (17.1)	
Overall height	L	mm (in)	1493 (58.8)
	UL	mm (in)	1620 (63.8)
Weight (without engine oil)	L	kg (lb)	162 (357.1)
	UL	kg (lb)	167 (368.2)
Transom height	L	mm (inch type)	520 (20)
	UL	mm (inch type)	647 (25)

PERFORMANCE

Maximum output	kW (PS)	44.1 (60)	51.5 (70)
Recommended operating range	r/min	4700 – 5300	5200 – 5800
Idle speed	r/min	700 ± 50 (in-gear: approx. 700)	

POWERHEAD

Engine type	4-stroke SOHC		
Number of cylinders	4		
Bore	mm (in)	74.0 (2.91)	
Stroke	mm (in)	75.5 (2.97)	
Total displacement	cm ³ (cu in)	1298 (79.2)	
Compression ratio	: 1	9.5	
Spark plug	NGK	BPR6ES	
Ignition system	Full-transistorized ignition		
Fuel supply system	Multi-point sequential electronic fuel injection		
Exhaust system	Through prop exhaust		
Cooling system	Water cooled		
Lubrication system	Wet sump by trochoid pump		
Starting system	Electric		
Throttle control	Remote control		Remote control