

SPECIFICATIONS

These specifications are subject to change without notice.

Item	Unit	Data					
		10R	10TE	10P	15R	15TE	15P

DIMENSIONS AND WEIGHT

Overall length (front to back)	mm (in)	1005 (39.6)						
Overall width (side to side)	mm (in)	320 (12.6)						
Overall height	S	mm (in)	1095 (43.1)					
	L	mm (in)	1220 (48.0)					
Weight	S	kg (lb)	44.0 (97.0)	47.5 (104.7)	46.5 (102.5)	44.0 (97.0)	47.5 (104.7)	46.5 (102.5)
	L	kg (lb)	45.0 (99.2)	48.5 (106.9)	47.5 (104.7)	45.0 (99.2)	48.5 (106.9)	47.5 (104.7)
Transom height	S	mm (in type) position	427 (15) [3]					
	L	mm (in type) position	554 (20) [3]					

PERFORMANCE

Maximum output	kW (HP)	7.3 (9.9)	11.0 (15)
Recommended operating range	rpm	4500 – 5500	5400 – 6000
Idle speed	rpm	1000 ± 50	

POWERHEAD

Engine type	4-stroke SOHC					
Number of cylinders	2					
Bore	mm (in)	58.0 (2.28)				
Stroke	mm (in)	57.0 (2.24)				
Total displacement	cm ³ (cu in)	302 (18.4)				
Compression ratio	: 1	9.0				
Spark plug	NGK	DCPR6E				
Intake system	Carburetor					
Exhaust system	Through prop hub exhaust					
Cooling system	Water cooled					
Lubrication system	Wet sump by trochoid pump					
Starting system	Manual	Electric		Manual	Electric	
Choke system	Manual		Electric	Manual		Electric
Throttle control	Twist grip		Remote control	Twist grip		Remote control
Ignition system	CDI					