

***SPECIFICATIONS**

* These specifications are subject to change without notice.

Item	Unit	Data	
		4 HP	5 HP

DIMENSIONS AND WEIGHT

Overall length (front to back)		mm (in)	554 (21.8): with tiller handle raised
Overall width (side to side)		mm (in)	309 (12.2)
Overall height	S	mm (in)	1064 (41.9)
	L	mm (in)	1191 (46.9)
Weight (without engine oil)	S	kg (lb)	26 (55.1)
	L	kg (lb)	27 (57.3)
Transom height	S	mm (inch type)	442 (15)
	L	mm (inch type)	569 (20)

PERFORMANCE

Maximum output	kW (PS)	2.9 (4)	3.7 (5)
Recommended operating range	r/min	4000 – 5000	4500 – 5500
Idle speed	r/min	1300 ± 50 (in-gear: approx: 1150)	

POWERHEAD

Engine type		4-stroke. OHV
Number of cylinders		1
Bore	mm (in)	62.0 (2.44)
Stroke	mm (in)	46.0 (1.81)
Total displacement	cm ³ (cu in)	138 (8.4)
Compression ratio	: 1	9.2
Spark plug	NGK	BPR6ES
Ignition system		(Digital CDI)
Fuel supply system		Carburetor
Exhaust system		Above prop exhaust
Cooling system		Water cooled
Lubrication system		Wet sump by trochoid pump
Starting system		Manual
Choke system		Manual
Throttle control		Twist grip