

# GENERAL INFORMATION SPECIFICATIONS

Item	Unit	Data					
		10R	10TE	10EL	15R	15TE	15EL

## FUEL AND OIL

Fuel	Bombardier highly recommends that you use alcohol-free unleaded gasoline with a minimum pump octane rating of 87 (R+M/2 method) or 91 (Research method). However, blends of unleaded gasoline and alcohol with equivalent octane content may be used.					
Engine oil	<i>Evinrude/Johnson Ultra Four Stroke Oil</i> or API classification: SE, SF, SG, SH, SJ (Viscosity rating: 10W-40)					
BREAK-IN OIL (FIRST 10 HOURS)	Evinrude/Johnson Four Stroke Oil					
Engine oil capacity	l (US/Imp. qt)	1.0 (1.1 / 0.9): Oil change only 1.1 (1.2 / 1.0): Oil filter change				
Gear oil	Ultra-HPF™ Gearcase Lubricant					
Gearcase oil capacity	ml (US/Imp. oz)	170 (5.7 / 6.0)				

## BRACKET

Trim angle	degree	4° - 20°
Number of trim position		5
Maximum tilt angle	degree	74°

## LOWER UNIT

Reversing system	Gear		
Transmission	Forward-Neutral-Reverse		
Reduction system	Bevel gear		
Gear ratio	12: 23 (1.92)		
Drive line impact protection	Spline drive rubber hub		
Propeller	Blade x Diam. (in) x Pitch (in)		
	3	x 9 1/4	x 7
	3	x 9 1/4	x 8
	3	x 9 1/4	x 9
	3	x 9 1/4	x 10
	3	x 9 1/4	x 11

These specifications are subject to change without notice.