

*SPECIFICATIONS

* These specifications are subject to change without notice.

Item	Unit	Data	
		4 HP	5 HP

DIMENSIONS AND WEIGHT

Overall length (front to back)	mm (in)	554 (21.8): with tiller handle raised	
Overall width (side to side)	mm (in)	309 (12.2)	
Overall height	S	mm (in)	1064 (41.9)
	L	mm (in)	1191 (46.9)
Weight (without engine oil)	S	kg (lb)	26 (55.1)
	L	kg (lb)	27 (57.3)
Transom height	S	mm (inch type)	442 (15)
	L	mm (inch type)	569 (20)

PERFORMANCE

Maximum output	kW (PS)	2.9 (4)	3.7 (5)
Recommended operating range	r/min	4000 – 5000	4500 – 5500
Idle speed	r/min	1300 ± 50 (in-gear: approx: 1150)	

POWERHEAD

Engine type	4-stroke. OHV		
Number of cylinders	1		
Bore	mm (in)	62.0 (2.44)	
Stroke	mm (in)	46.0 (1.81)	
Total displacement	cm ³ (cu in)	138 (8.4)	
Compression ratio	: 1	9.2	
Spark plug	NGK	BPR6ES	
Ignition system	(Digital CDI)		
Fuel supply system	Carburetor		
Exhaust system	Above prop exhaust		
Cooling system	Water cooled		
Lubrication system	Wet sump by trochoid pump		
Starting system	Manual		
Choke system	Manual		
Throttle control	Twist grip		