

SPECIFICATIONS

These specifications are subject to change without notice.

Item	Unit	Data					
		10R	10TE	10EL	15R	15TE	15EL

DIMENSIONS AND WEIGHT

Overall length (front to back)	mm (in)	1005 (39.6)						
Overall width (side to side)	mm (in)	320 (12.6)						
Overall height	S	mm (in)	1095 (43.1)					
	L	mm (in)	1220 (48.0)					
Weight	S	kg (lb)	44.0 (97.0)	47.5 (104.7)	46.5 (102.5)	44.0 (97.0)	47.5 (104.7)	46.5 (102.5)
	L	kg (lb)	45.0 (99.2)	48.5 (106.9)	47.5 (104.7)	45.0 (99.2)	48.5 (106.9)	47.5 (104.7)
Transom height	S	mm (in type) position	427 (15) [3]					
	L	mm (in type) position	554 (20) [3]					

PERFORMANCE

Maximum output	kW (HP)	7.3 (9.9)	11.0 (15)
Recommended operating range	rpm	4500 – 5500	5400 – 6000
Idle speed	rpm	1100 ± 50	
In-gear idle speed	rpm	Approx. 1000	

POWERHEAD

Engine type	4-stroke SOHC			
Number of cylinders	2			
Bore	mm (in)	58.0 (2.28)		
Stroke	mm (in)	57.0 (2.24)		
Total displacement	cm ³ (cu in)	302 (18.4)		
Compression ratio	: 1	9.0		
Spark plug	NGK	DCPR6E		
Intake system	Carburetor			
Exhaust system	Through prop hub exhaust			
Cooling system	Water cooled			
Lubrication system	Wet sump by trochoid pump			
Starting system	Manual	Electric	Manual	Electric
Choke system	Manual	Electric	Manual	Electric
Throttle control	Twist grip	Remote control	Twist grip	Remote control
Ignition system	CDI			