

# SPECIFICATIONS

Specifications are subject to change without notice.

1

Item	Unit	Data		
		200	225	250

## DIMENSIONS & WEIGHT

Overall length (front to back)		in. (mm)	35.3 (897)
Overall width (side to side)		in. (mm)	22.5 (572)
Overall height	UL	in. (mm)	72.2 (1834)
Weight (without engine oil)	UL	lbs. (kg)	580 (263)
Transom height	UL	in. (mm)	25 (632)

## PERFORMANCE

Maximum output	kW (PS)	147 kW (200)	165 kW(225)	184 (250)
Recommended operating range	RPM	5 000 – 6 000 RPM	5 000 – 6 000 RPM	5 500 – 6 100 RPM
Idle speed	RPM	650 ± 50 (in-gear: Approx. 650)		

## POWER HEAD

Engine type	4-stroke DOHC		
Number of cylinders	V-6		
Bore	in. (mm)	3.74 (95)	
Stroke	in. (mm)	3.35 (85)	
Total displacement	cu. in. (cm <sup>3</sup> )	220.5 (3614)	
Compression ratio	: 1	9.5	
Spark plug		NGK: BKR6E	
Ignition system		Full-transistorized ignition	
Fuel supply system		Multi-point sequential electronic fuel injection	
Exhaust system		Through prop exhaust	
Cooling system		Water cooled	
Lubrication system		Wet sump by trochoid pump	
Starting system		Electric	
Throttle control		Remote control	