

*SPECIFICATIONS

* These specifications are subject to change without notice.

Item	Unit	Data		
		4 HP	5 HP	6 HP

DIMENSIONS AND WEIGHT

Overall length (front to back)		mm (in)	554 (21.8): with tiller handle raised	
Overall width (side to side)		mm (in)	309 (12.2)	
Overall height	S	mm (in)	1064 (41.9)	
	L	mm (in)	1191 (46.9)	
Weight (without engine oil)	S	kg (lb)	26 (55.1)	
	L	kg (lb)	27 (57.3)	
Transom height	S	mm (inch type)	442 (15)	
	L	mm (inch type)	569 (20)	

PERFORMANCE

Maximum output		kW (PS)	2.9 (4)	3.7 (5)	4.4 (6)
Recommended operating range		r/min	4000 – 5000	4500 – 5500	4750 – 5750
Idle speed		r/min	1300 ± 50 (in-gear: approx: 1150)		1300 ± 50 (in-gear: approx: 1200)

POWERHEAD

Engine type		4-stroke OHV		
Number of cylinders		1		
Bore		mm (in)	62.0 (2.44)	
Stroke		mm (in)	46.0 (1.81)	
Total displacement		cm ³ (cu in)	138 (8.4)	
Compression ratio		: 1	9.2	
Spark plug		NGK	BPR6ES	
Ignition system		Electronic Ignition (Digital CDI)		
Fuel supply system		Carburetor		
Exhaust system		Above prop exhaust		
Cooling system		Water cooled		
Lubrication system		Wet sump by trochoid pump		
Starting system		Manual		
Choke system		Manual		
Throttle control		Twist grip		