

SPECIFICATIONS

Item	Unit	Data	
		40PL4	50PL4

DIMENSIONS AND WEIGHT

Overall length (front to back)	mm (in)	756 (29.8)	
Overall width (side to side)	mm (in)	382 (15.0)	
Overall height	S	mm (in)	1263 (49.7)
	L	mm (in)	1390 (54.7)
Weight (without engine oil)	S	kg (lbs)	106 (234)
	L	kg (lbs)	109 (240)
Transom height	S	mm (in type)	401 (15)
	L	mm (in type)	528 (20)

PERFORMANCE

Maximum output	kW (HP)	29.4 (40)	36.8 (50)
Recommended operating range	r/min	5200 – 5800 (E.U. model: 5600 – 6200)	5900 – 6500 (All models)
Idle speed	r/min	850 ± 50 (in-gear: approx. 850)	

POWERHEAD

Engine type	4-stroke DOHC		
Number of cylinders	3		
Bore	mm (in)	71.0 (2.80)	
Stroke	mm (in)	68.6 (2.70)	
Total displacement	cm ³ (cu in)	815 (49.7)	
Compression ratio	10:1		
Spark plug	NGK	DCPR6E	
Ignition system	Full-transistorized ignition		
Fuel supply system	Multi-point sequential electronic fuel injection		
Exhaust system	Through prop exhaust		
Cooling system	Water cooled		
Lubrication system	Wet sump by trochoid pump		
Starting system	Electric		
Throttle control	Remote control (optional tiller kit)		