

*SPECIFICATIONS

* These specifications are subject to change without notice.

Item	Unit	Data		
		4 HP	5 HP	6 HP

DIMENSIONS AND WEIGHT

Overall length (front to back)	mm (in)	554 (21.8): with tiller handle raised		
Overall width (side to side)	mm (in)	309 (12.2)		
Overall height	S	mm (in)	1064 (41.9)	
	L	mm (in)	1191 (46.9)	
Weight (without engine oil)	S	kg (lb)	26 (55.1)	
	L	kg (lb)	27 (57.3)	
Transom height	S	mm (inch type)	442 (15)	
	L	mm (inch type)	569 (20)	

PERFORMANCE

Maximum output	kW (PS)	2.9 (4)	3.7 (5)	4.4 (6)
Recommended operating range	r/min	4000 – 5000	4500 – 5500	4750 – 5750
Idle speed	r/min	1300 ± 50 (in-gear: approx: 1150)		1300 ± 50 (in-gear: approx: 1200)

POWERHEAD

Engine type	4-stroke OHV			
Number of cylinders	1			
Bore	mm (in)	62.0 (2.44)		
Stroke	mm (in)	46.0 (1.81)		
Total displacement	cm ³ (cu in)	138 (8.4)		
Compression ratio	: 1	9.2		
Spark plug	NGK	BPR6ES		
Ignition system	Electronic Ignition (Digital CDI)			
Fuel supply system	Carburetor			
Exhaust system	Above prop exhaust			
Cooling system	Water cooled			
Lubrication system	Wet sump by trochoid pump			
Starting system	Manual			
Choke system	Manual			
Throttle control	Twist grip			