

Electric Outboard Specifications

1989 Models

	TH2Y	BH2TY (BHL2TY)	BHL4Y	BF2Y	BF2TY BFL2TY BFX2TY	BF4Y BFL4Y BFX4Y
Mounting	Transom	Deck	Deck	Deck	Deck	Deck
Steering Control	Hand	Hand	Hand	Foot	Foot	Foot
Motor	Permanent Magnet	Permanent Magnet	Permanent Magnet	Permanent Magnet	Permanent Magnet	Permanent Magnet
Static Thrust	23 lbs.	26 lbs.	33 lbs.	21 lbs.	23 lbs.	31 lbs.
Maximum Current Draw	34 amps	36 amps	33 amps	31 amps	33 amps	29 amps
Operating Voltage	12V	12V	12/24V	12V	12V	12/24V
Speed Control	4	4	6	3	3	6
Propeller Size	8 $\frac{3}{8}$ " x 4"	12 $\frac{1}{2}$ " x 4"W	8 $\frac{3}{4}$ " x 4"W	8 $\frac{3}{8}$ " x 4"	12 $\frac{1}{2}$ " x 4"W	8 $\frac{3}{4}$ " x 4"W
Weight - lbs.	16	L 25 26	26	28	L X 28 30 31	L X 28 29 31
Shaft Length - in.	36	36 42	42	36	36 42 48	36 42 48
Cable Length - ft.	None	None	None	5	5 5 8	5 8 8
Directional Indicator	None	None	None	Yes	Yes	Yes
Indicator Bulb	None	None	None	319593	319593	320457
Overload Protection	Yes	Yes	No	No	No	No