

## Specifications, Hand Control Models

Models	TH2T	TH4T	BH2T	BHL2T	BHL4	BHL4T
Mounting	Transom; Double Clamp Screw	Transom; Double Clamp Screw	Deck; Bolt-On	Deck; Bolt-On	Deck; Bolt-On	Deck; Bolt-On
Steering Control	Hand	Hand	Hand	Hand	Hand	Hand
Voltage	12 V	12/24 V	12 V	12 V	12/24 V	12/24 V
Static Thrust	32 lbs.	58 lbs.	32 lbs.	32 lbs.	43 lbs.	58 lbs.
Maximum Operating Current Draw	<b>34 Amps</b>	30 Amps	36 Amps	36 Amps	33 Amps	30 Amps
Motor Type (Sealed)	Permanent Magnet	Permanent Magnet	Permanent Magnet	Permanent Magnet	Permanent Magnet	Permanent Magnet
Speed Control	4 Speeds + Jog	6 Speeds + Jog	4 Speeds + Jog	4 Speeds + Jog	6 Speeds + Jog	6 Speeds + Jog
Weight (pounds)	16	20	24.5	26	26	29
Shaft Length (inches)	36	36	36	42	42	42
Vertical Adjustment (inches)	20	20	19	19	25	25
Steering Cable Length (feet)	None	None	None	None	None	None
Indicator Bulb	None	None	None	None	None	None
2-Blade Propeller	12½" x 4" Weedless	12" x 3" Weedless	12½" x 4" Weedless	12½" x 4" Weedless	8¾" x 4" Weedless	12" x 3" Weedless
Battery*, Ampere-Hour (Minimum)	One; 80 Deep Cycle	Two; 80 Deep Cycle	One; 80 Deep Cycle	One; 80 Deep Cycle	Two; 80 Deep Cycle	Two; 80 Deep Cycle
Overload Protection	Yes	No	Yes	Yes	No	No

\*Use of a battery greater than 80 Ampere-Hours improves motor performance and battery life.

## Specifications, Foot Control Models

Models	BF2	BF2T (BFL2T)	BFX2T	BF4 (BFL4)	BFX4	BF4T (BFL4T)	BFX4T
Mounting	Deck; Bolt-On	Deck; Bolt-On	Deck; Bolt-On	Deck; Bolt-On	Deck; Bolt-On	Deck; Bolt-On	Deck; Bolt-On
Steering Control	Foot	Foot	Foot	Foot	Foot	Foot	Foot
Voltage	12 V	12 V	12 V	12/24 V	12/24 V	12/24 V	12/24 V
Static Thrust	26 lbs.	29 lbs.	29 lbs.	41 lbs.	41 lbs.	56 lbs.	56 lbs.
Maximum Operating Current Draw	31 Amps	33 Amps	33 Amps	29 Amps	29 Amps	29 Amps	29 Amps
Motor Type (Sealed)	Permanent Magnet	Permanent Magnet	Permanent Magnet	Permanent Magnet	Permanent Magnet	Permanent Magnet	Permanent Magnet
Speed Control	3 Speeds	3 Speeds	3 Speeds	6 Speeds	6 Speeds	6 Speeds	6 Speeds
Weight (pounds)	28	28 (29.5)	31	27.5 (29)	30.5	30.5 (32)	33.5
Shaft Length (inches)	36	36 (42)	48	36 (42)	48	36 (42)	48
Vertical Adjustment (inches)	15	15	21	15	21	15	21
Steering Cable Length (feet)	5	5	8	5	8	5	8
Indicator Bulb	319593	319593	319593	320457	320457	320457	320457
2-Blade Propeller	8 $\frac{3}{8}$ " x 4" Standard	12 $\frac{1}{2}$ " x 4" Weedless	12 $\frac{1}{2}$ " x 4" Weedless	8 $\frac{3}{4}$ " x 4" Weedless	8 $\frac{3}{4}$ " x 4" Weedless	12" x 3" Weedless	12" x 3" Weedless
Battery*, Ampere-Hour (Minimum)	One; 80 Deep Cycle	One; 80 Deep Cycle	One; 80 Deep Cycle	Two; 80 Deep Cycle	Two; 80 Deep Cycle	Two; 80 Deep Cycle	Two; 80 Deep Cycle
Overload Protection	No	No	No	No	No	No	No

\*Use of a battery greater than 80 Ampere-Hours improves motor performance and battery life.