

Specifications, Hand Control Models

Models	TH2T	TH4T	BH2T/BHL2T	BHL4	BHL4T
Mounting	Transom Clamp	Transom Clamp	Deck – Bolt On	Deck – Bolt On	Deck – Bolt On
Steering Control	Hand	Hand	Hand	Hand	Hand
Voltage	12 V.	12/24 V.	12 V.	12/24 V.	12/24 V.
Static Thrust	32 lbs.	58 lbs.	32 lbs.	43 lbs.	58 lbs.
Maximum Current	36 Amps	30 Amps	36 Amps	33 Amps	30 Amps
Motor Type	Permanent Magnet	Permanent Magnet	Permanent Magnet	Permanent Magnet	Permanent Magnet
Speed Control	4 Speeds + Jog	6 Speeds + Jog	4 Speeds + Jog	6 Speeds + Jog	6 Speeds + Jog
Weight (pounds)	16	20	24.5/26	26	29
Shaft Length (inches)	36	36	36/42	42	42
Vertical Adj. (inches)	20	20	19/19	25	25
Propeller-Standard 2-Blade OMC P/N	12½" x 4" Weedless 331707†	12½" x 4" Weedless 331707†	12½" x 4" Weedless 331707†	8¾" x 4" Weedless 124709	12½" x 4" Weedless 331707†
Battery – Type	Deep Cycle (1)	Deep Cycle (2)	Deep Cycle (1)	Deep Cycle (2)	Deep Cycle (2)
Ampere-Hour *	80	80	80	80	80
Overload Protection	Yes	Yes	Yes	Yes	Yes

† Use weedless propeller P/N 126583 for operation in heavy vegetation.

* Minimum requirement, using a battery rated higher than 80 ampere-hours improves motor performance and battery life.

Specifications, Foot Control Models

Models	HBF2	BF2	BF2T/BFL2T /BFX2T	BF4/BFL4 /BFX4	BF4T/BFL4T /BFX4T
Mounting	Deck – Bolt On Foot	Deck – Bolt On Foot	Deck – Bolt On Foot	Deck – Bolt On Foot	Deck – Bolt On Foot
Steering Control	Foot	Foot	Foot	Foot	Foot
Voltage	12 V.	12 V.	12 V.	12/24 V.	12/24 V.
Static Thrust	26.5 lbs.	26 lbs.	29 lbs.	41 lbs.	56 lbs.
Maximum Current	34 Amps	31 Amps	33 Amps	29 Amps	29 Amps
Motor Type	Permanent Magnet	Permanent Magnet	Permanent Magnet	Permanent Magnet	Permanent Magnet
Speed Control	3 Speeds	3 Speeds	3 Speeds	6 Speeds	6 Speeds
Weight (pounds)	26.4	28	28/29.5/31	27.5/29/30.5	30.5/32/33.5
Shaft Length (inches)	36	36	36/42/48	36/42/48	36/42/48
Vertical Adj. (inches)	7.5	15	15/15/21	15/15/21	15/15/21
Steering Cable (feet)	5	5	5/5/8	5/5/8	5/5/8
Indicator Bulb	None	319593	319593	320457	320457
Propeller-Standard 2-Blade OMC P/N	8 ³ / ₄ " x 3.8" – 115827	8 ³ / ₈ " x 4" – 327530	12 ¹ / ₂ " x 4" Weedless 331707†	8 ³ / ₄ " x 4" Weedless 124709	12 ¹ / ₂ " x 4" Weedless 331707†
Battery – Type Ampere-Hour *	Deep Cycle (1) 80	Deep Cycle (1) 80	Deep Cycle (1) 80	Deep Cycle (2) 80	Deep Cycle (2) 80

† Use weedless propeller P/N 126583 for operation in heavy vegetation.

* Minimum requirement, using a battery rated higher than 80 ampere-hours improves motor performance and battery life.