

## Engine Specifications

### 2, 2.3, 3.3

#### Operation

---

Full Throttle Operating Range	<b>2</b> – 4000 to 5000 RPM <b>2.3</b> – 4200 to 5200 RPM <b>3.3</b> – 4500 to 5500 RPM
Power	<b>2</b> – 2 HP (1,5 kw) <b>2.3</b> – 2.3 HP (1,7 kw) <b>3.3</b> – 3.3 HP (2,5 kw)
Power Rate	<b>2</b> – 4500 RPM <b>2.3</b> – 4700 RPM <b>3.3</b> – 5000 RPM
Idle RPM in Gear	1200 ± 100
Test Propeller	<b>2, 2.3</b> – <b>OMC</b> Standard Propeller P/N 115208 <b>3.3</b> – <b>OMC</b> P/N 115306
Minimum Test RPM	<b>2</b> – 4500 <b>2.3</b> – 4800 <b>3.3</b> – 5000
Weight	29.7 lbs. (13,5 kg)

#### Powerhead

---

Type	Single Cylinder
Displacement	4.75 cu. in. (77,8 cm <sup>3</sup> )
Bore	1.8898 (48 mm)
Stroke	1.6929 (43 mm)
Standard Bore	1.8890 - 1.8906 in. (48,00 - 48,02 mm)
Crankshaft Dimensions	
Top Journal	0.7875 - 0.7878 in. (20,002 - 20,010 mm)
Bottom Journal	0.5906 - 0.5910 in. (15,001 - 15,011 mm)
Rod Crankpin	0.6299 - 0.6301 in. (16,00 - 16,005 mm)
Piston Diameter, Standard	1.8868 - 1.8873 in. (47,9247 - 47,9374 mm)
Piston Ring End Gap	0.0059 - 0.0138 in. (0,15 - 0,35 mm)
Piston Ring Groove Side Clearance	0.0026 in. (0,066 mm) maximum

## Engine Specifications 3, 4

### Operation

---

Full Throttle Operating Range	4500 to 5500 RPM
Power	3 – 3 HP (2,2 kw) 4 – 4 HP (3 kw)
Power Rated @	5000 RPM
Idle RPM in Gear	750 ± 50
Test Propeller	OMC P/N 317738
Minimum Test RPM	4400
Weight	R – 33 lbs. (15,0 kg) RL – 35 lbs. (16,0 kg)

### Powerhead

---

Type	In-line 2-Cylinder
Displacement	5.28 cu. in. (87 cm <sup>3</sup> )
Bore	1.565 in. (39,7 mm)
Stroke	1.374 in. (34,9 mm)
Standard Bore *	1.5643 - 1.5650 in. (39,74 - 39,75 mm)
Crankshaft Dimensions	
Top Journal	0.7515 - 0.7520 in. (19,08 - 19,10 mm)
Center Journal	0.6685 - 0.6690 in. (16,98 - 16,99 mm)
Bottom Journal	0.6691 - 0.6695 in. (17,00 - 17,01 mm)
Rod Crankpin	0.6695 - 0.6700 in. (17,01 - 17,02 mm)
Piston Diameter, Standard	1.5625 - 1.5631 in. (39,69 - 39,70 mm)
Piston Ring End Gap, Both	0.005 - 0.015 in. (0,13 - 0,38 mm)
Piston Ring Groove Side Clearance, Both	0.004 in. (0,10 mm) maximum

\* To bore oversize, add piston oversize dimension to standard bore.

## Engine Specifications 5 thru 8

### Operation

Full Throttle Operating Range	<b>5, 6</b> – 4500 to 5500 RPM <b>8</b> – 5000 to 6000 RPM
Power	<b>5</b> – 5 HP (3,7 kw) <b>6</b> – 6 HP (4,5 kw) <b>8</b> – 8 HP (6 kw)
Power Rated @	<b>5, 6</b> – 5000 RPM <b>8</b> – 5500 RPM
Idle RPM in Gear	700 ± 25 <b>6SL, 8SRL</b> – 900 ± 25
Test Propeller	<b>OMC</b> P/N 390239
Minimum Test RPM	<b>5</b> – 4500 <b>6</b> – 4800 <b>8</b> – 5300 <b>8SRL</b> – 4850
Weight	<b>R, BA</b> – 56 lbs. (25,4 kg) <b>RL, BAL</b> – 58.5 lbs. (26,5 kg) <b>6SL</b> – 61.3 lbs. (27,4 kg) <b>8SRL</b> – 64 lbs. (29 kg)

### Powerhead

Type	In-Line 2-Cylinder
Displacement	10 cu. in. (164 cm <sup>3</sup> )
Bore	1.9375 in. (49,21 mm)
Stroke	1.700 in. (43,18 mm)
Standard Bore *	1.9373 - 1.9380 in. (49,21 - 49,23 mm)
Crankshaft Dimensions:	
Top Journal	0.8762 - 0.8767 in. (22,26 - 22,27 mm)
Center Journal	0.8120 - 0.8125 in. (20,62 - 20,64 mm)
Bottom Journal	0.6691 - 0.6695 in. (17,00 - 17,01 mm)
Rod Crankpin	0.6695 - 0.6700 in. (17,01 - 17,02 mm)
Piston Diameter, Standard	1.9345 - 1.9355 in. (49,14 - 49,16 mm)
Piston Ring End Gap, Both	0.005 - 0.015 in. (0,13 - 0,38 mm)
Piston Ring Groove Side Clearance, Both	0.004 in. (0,10 mm) maximum

\* To bore oversize, add piston oversize dimension to standard bore.