

Engine Specifications

9.9/15

Operation

Full Throttle Operating Range	5000 to 6000 RPM
Power	9.9 – 9.9 HP (7,4 kw) 15 – 15 HP (11,2 kw)
Power Rated @	5500 RPM
Idle RPM in Gear	700 ± 25
Test Propeller	OMC P/N 340177
Minimum Test RPM	9.9 – 4900 15 – 5700 SEL – 3500
Weight	R – 72 lbs. (33 kg) RL – 77 lbs. (35 kg) E – 75 lbs. (34,4 kg) EL, REL – 80 lbs. (36,4 kg) 9.9 SEL – 88 lbs. (40 kg)

Powerhead

Type	In-line 2-Cylinder
Displacement	15.6 cu. in. (255 cm ³)
Bore	2.375 in. (60,33 mm)
Stroke	1.760 in. (44,70 mm)
Standard Bore*	2.3745 - 2.3750 in. (60,31 - 60,33 mm)
Crankshaft Dimensions:	
Top Journal	0.8757 - 0.8762 in. (22,24 - 22,26 mm)
Center Journal	0.8120 - 0.8125 in. (20,63 - 20,64 mm)
Bottom Journal	0.7870 - 0.7874 in. (19,98 - 19,99 mm)
Rod Crankpin	0.8120 - 0.8125 in. (20,63 - 20,64 mm)
Piston Ring End Gap, Both	0.005 - 0.015 in. (0,13 - 0,38 mm)
Piston Ring Groove Side Clearance, Lower	0.004 in. (0,10 mm) maximum

*To bore oversize, add piston oversize dimension to standard bore.

Engine Specifications 10/15 Comm.

Operation

Full Throttle Operating Range	5000 to 6000 RPM
Power	10 – 9.9 HP (7,4 kw) 15 – 15 HP (11,2 kw)
Power Rated @	5500 RPM
Idle RPM in Gear	700 ± 25 15 KC – 1000 ± 100
Test Propeller	OMC P/N 340177 15 KC – OMC P/N 386537
Minimum Test RPM	10 – 4900 15 – 5700
Weight	RP, KC – 72 lbs. (33 kg) RPL, KCL – 77 lbs. (35 kg)

Powerhead

Type	In-line 2-Cylinder
Displacement	15.6 cu. in. (255 cm ³)
Bore	2.375 in. (60,33 mm)
Stroke	1.760 in. (44,70 mm)
Standard Bore*	2.3745 - 2.3750 in. (60,31 - 60,33 mm)
Crankshaft Dimensions:	
Top Journal	0.8757 - 0.8762 in. (22,24 - 22,26 mm)
Center Journal	0.8120 - 0.8125 in. (20,63 - 20,64 mm)
Bottom Journal	0.7870 - 0.7874 in. (19,98 - 19,99 mm)
Rod Crankpin	0.8120 - 0.8125 in. (20,63 - 20,64 mm)
Piston Ring End Gap, Both	0.005 - 0.015 in. (0,13 - 0,38 mm)
Piston Ring Groove Side Clearance, Lower	0.004 in. (0,10 mm) maximum

*To bore oversize, add piston oversize dimension to standard bore.

Engine Specifications 20 thru 30

Operation

Full Throttle Operating Range	20, 25, 25 Comm. – 4500 to 5500 RPM 30 – 5200 to 5800 RPM
Power	20 – 20 HP (14,9 kw) 25 – 25 HP (18,7 kw) 30 – 30 HP (22,4 kw)
Power Rated @	20, 25 – 5000 RPM 30 – 5500 RPM
Idle RPM in Gear	675 ± 25
Test Propeller	20 – OMC P/N 386891 25, 30 – OMC P/N 434505*
Minimum Test RPM	20 – 4550 25 – 4800 25 Comm. – 4800 30 – 5400
Weight	R – 114 lbs. (51,8 kg) Long Shaft – Add 2 lbs. (0,9 kg) TE – 120 lbs. (54,5 kg) Long Shaft – Add 2 lbs. (0,9 kg) E – 118 lbs. (53,6 kg) Long Shaft – Add 2 lbs. (0,9 kg)

*Test Propeller P/N 394145 can be used if trim tab is removed.

Powerhead

Type	In-line 2-Cylinder
Displacement	31.8 cu. in. (521 cm ³)
Bore	3.000 in. (76,20 mm)
Stroke	2.250 in. (57,15 mm)
Standard Bore*	2.9995 - 3.0005 in. (76,19 - 76,21 mm)
Crankshaft Dimensions:	
Top Journal	1.2510 - 1.2515 in. (31,78 - 31,79 mm)
Center Journal	1.1833 - 1.1838 in. (30,06 - 30,07 mm)
Bottom Journal	0.9842 - 0.9846 in. (25,00 - 25,01 mm)
Rod Crankpin	1.1823 - 1.1828 in. (30,03 - 30,04 mm)
Piston Diameter, Standard	See Section 4
Piston Ring End Gap, Both	0.007 - 0.017 in. (0,18 - 0,43 mm)
Piston Ring Groove Side Clearance, Lower	0.004 in. (0,10 mm) maximum

*To bore oversize, add piston oversize dimension to standard bore.