

General specifications

Item	Unit	Model	
		F50TR	T50TR
Dimension			
Overall length	mm (in)	718 (28.3)	
Overall width	mm (in)	361 (14.2)	
Overall height (L)	mm (in)	1,397 (55.0)	1,463 (57.6)
Boat transom height (L)	mm (in)	508 (20.0)	
Weight (without propeller) (L)	kg (lb)	106 (234)	110 (243)
Performance			
Maximum output	kW (hp) @ 5,500 r/min	36.8 (50)	
Full throttle operating range	r/min	5,000–6,000	
Maximum fuel consumption	L (US gal, Imp gal)/hr @ 6,000 r/min	17.3 (4.57, 3.81)	
Power unit			
Type		In-line, 4-stroke, OHC, 8 valves	
Cylinder quantity		4	
Displacement	cm ³ (cu. in)	935 (57.1)	
Bore × stroke	mm (in)	63.0 × 75.0 (2.48 × 2.95)	
Compression ratio		9.3	
Carburetor quantity		4	
Control system		Remote control	
Starting system		Electric	
Ignition control system		Microcomputer (CDI)	
Ignition timing	Degree	BTDC 5–BTDC 35	TDC–BTDC 30
Alternator output	V, A	12, 10	
Enrichment system		Prime Start	
Choke valve control		—	
Spark plugs		DPR6EA-9 (NGK)	
Cooling system		Water	
Exhaust system		Through propeller boss	
Lubrication system		Wet sump	

General specifications



Item	Unit	Model	
		F50TR	T50TR
Fuel and oil		Regular unleaded gasoline	
Fuel type		86	
Fuel rating	PON ^(*1) RON	91	
Engine oil type		4-stroke motor oil	
Engine oil grade	API SAE	SE, SF, SG, SH, or SJ 10W-30 or 10W-40	
Engine oil quantity (with oil filter replacement)	L (US qt, Imp qt)	2.2 (2.3, 1.9)	
(without oil filter replacement)	L (US qt, Imp qt)	2.0 (2.1, 1.8)	
Gear oil type		GEAR CASE LUBE	
Gear oil grade	SAE	90	
Gear oil quantity	L (US qt, Imp qt)	0.43 (0.45, 0.38)	0.67 (0.71, 0.59)
Bracket			
Trim angle (at 12 degree boat transom)	Degree	-4-20	
Tilt-up angle	Degree	69	
Steering angle	Degree	40 + 40	
Drive unit		F-N-R	
Gear shift positions			
Gear ratio		1.85 (24/13)	2.31 (30/13)
Reduction gear type		Spiral bevel gear	
Clutch type		Dog clutch	
Propeller shaft type		Spline	
Propeller direction (rear view)		Clockwise	
Propeller identification mark		G	K
Electrical			
Battery minimum capacity ^(*2)			
CCA/SAE	A	380	
MCA/ABYC	A	502	
RC/SAE	Minute	124	

(*1) PON: Pump Octane Number = (RON + Motor Octane Number)/2

RON: Research Octane Number

(*2) CCA: Cold Cranking Ampere

MCA: Marine Cranking Ampere

ABYC: American Boat and Yacht Council

SAE: Society of Automotive Engineers

RC: Reserve Capacity